

K202-K210 Combination Refrigerators & Freezers

USES: / CLINICAL APPLICATIONS / VACCINES & MEDICATIONS / BIOLOGICS / DIAGNOSTICS KITS / MOLECULAR BIOLOGY / INDUSTRIAL TESTING

K2 Scientific's compact 2.5 cu. ft. and 10 cu. ft. refrigerators and freezer are perfect for storing vaccines. Engineered with precision, these refrigerators are meticulously crafted to optimize space utilization without compromising on performance. Their small footprint design makes them an ideal choice for facilities with space constraints, where every square inch matters. We do not recommend stacking these units. Shorter staff members may find it difficult to reach the 2.5 cu. ft. unit when stacked on the 10 cu. ft. unit.



K210GDR-K202SDF

K210SDR-K202SDF

K202GDR-K210SDF

K202SDR-K210SDF

- Intelligent microprocessor controller with digital display and adjustable temperature control
- Static (cycle) defrost
- Audible and visual high or low temperature alarms
- Magnetically sealed door with rapid cool-down mode after door opening
- Efficient, exterior, switch-activated interior LED lighting
- Remote alarm contacts
- Adjustable white epoxy-coated wire shelves standard
- Keyed door lock
- Shelves are adjustable by 1-inch increments
- Cabinet constructed of white powder-coated steel with CFC-free, high density insulation
- An environmentally green, compliant with future EPA and SNAP mandates
- Forced air circulation aids temperature stability and uniformity
- 0.5" temperature probe and data logger access port
- Built and shipped from ISO 9001:2015 manufacturing and distribution facilities
- Three quality control checks prior to shipping
- Warranty: Two-year parts, labor, or full replacement

MODEL NUMBER	CAPACITY CU. FT.	EXTERIOR Depth x Width x Height	INTERIOR Depth x Width x Height	TEMP RANGE (SETPOINT)	DOORS	SHELVES	DEFROST	SHIPPING WT. LBS.
K202GDR/SDR	2.5	22.5" x 20.1" x 25.75"	15.5" x 15.5" x 16"	+2°C to +8°C (+4°C)	1	2	STATIC (CYCLE)	100/94 lbs
K202SDF	2.5	22.5" x 20.1" x 25.75"	15.5" x 15.5" x 16"	-10°C to -25°C (-20°C)	1	2	MANUAL	94 lbs
K210GDR/SDR	10	22.5" x 23.6" x 60.2"	15" x 19.5" x 50.5"	+2°C to +8°C (+4°C)	1	6	STATIC (CYCLE)	185/168 lbs
K210SDF	10	22.5" x 23.6" x 60.2"	15" x 19.5" x 50.5"	-10°C to -30°C (-20°C)	1	6	MANUAL	168 lbs

Model #	K202GDR/SDR	K202SDF	K210GDR/SDR	K210SDF
Storage Volume	2.5 cubic feet	2.5 cubic feet	10 cubic feet	10 cubic feet
Specifications				
Exterior (D x W x H)	22.5" x 20.1 x 25.75"	22.5" x 20.1 x 25.75"	22.5" x 23.6" x 60.2"	22.5" x 23.6" x 60.2"
Interior (D x W x H)	15.5" x 15.5" x 16"	15.5" x 15.5" x 16"	15" x 19.5" x 50.5"	15" x 19.5" x 50.5"
Insulation	CFC-free, high density insulation	CFC-free, high density insulation	CFC-free, high density insulation	CFC-free, high density insulation
Doors	1, right-hand swing	1, right-hand swing	1, right-hand swing	1, right-hand swing
Shelves	2	2	6	6
Access Port	0.5" probe port	0.5" probe port	0.5" probe port	0.5" probe port
Leveling Legs	Standard	Standard	Standard	Standard
Shipping Weight	100/94 lbs	94 lbs	185/168 lbs	168 lbs
Certifications & Compliances	cULus, ISO: 9001:2015, Energy Star, CDC and VFC Compliant, EPA and SNAP Compliant	cULus, ISO: 9001:2015, Energy Star, CDC and VFC Compliant, EPA and SNAP Compliant	cULus, ISO: 9001:2015, Energy Star, CDC and VFC Compliant, EPA and SNAP Compliant	cULus, ISO: 9001:2015, Energy Star, CDC and VFC Compliant, EPA and SNAP Compliant
Performance				
Stability	+/- 2°C to 3°C	+/- 2°C to 3°C	+/- 2°C to 3°C	+/- 2°C to 3°C
Adjustable Set Point Range	+2°C to +8°C	-10°C to -25°C	+2°C to +8°C	-10°C to -30°C
Factory Set Point	+4°C	-20°C	+4°C	-20°C
Electrical Power/Current	120v 60 Hz 15 Amp	120v 60 Hz 15 Amp	120v 60 Hz 15 Amp	120v 60 Hz 15 Amp
Power Plug	NEMA 5-15	NEMA 5-15	NEMA 5-15	NEMA 5-15
Indoor/Outdoor Use	Indoor use only	Indoor use only	Indoor use only	Indoor use only
Application Environment	Non-corrosive, non-flammable, non-explosive	Non-corrosive, non-flammable, non-explosive	Non-corrosive, non-flammable, non-explosive	Non-corrosive, non-flammable, non-explosive
Ambient Operating Temp	20°C to 32°C	20°C to 32°C	20°C to 32°C	20°C to 32°C
Refrigeration				
Refrigeration System	Vapor compression system, forced-air	Vapor compression system	Vapor compression system, forced-air	Vapor compression system
Compressor	Hemetically sealed compressor	Hemetically sealed compressor	Hemetically sealed compressor	Hemetically sealed compressor
Condenser Type	Foamed in	Foamed in	Foamed in	Foamed in
Expansion Device	Capillary tube	Capillary tube	Capillary tube	Capillary tube
Evaporator Type	Forced-air	Cold wall evaporator	Forced-air	Cold wall evaporator
Defrost	Static (cycle)	Manual	Static (cycle)	Manual
Refrigerant	R600a (Isobutane)	R600a (Isobutane)	R600a (Isobutane)	R600a (Isobutane)
Controller/System Configuration				
User Interface	Microprocessor with digital display	Microprocessor with digital display	Microprocessor with digital display	Microprocessor with digital display
Power Switch	Plug & Play	Plug & Play	Plug & Play	Plug & Play
Controller Type	Digital Controller	Digital Controller	Digital Controller	Digital Controller
Security	Keyed lockable doors	Keyed lockable doors	Keyed lockable doors	Keyed lockable doors
Control Sensor	NTC probe	NTC probe	NTC probe	NTC probe
Remote Alarm Terminals	Standard	Standard	Standard	Standard
High/Low Alarms	Standard	Standard	Standard	Standard
Power Failure Alarm	Standard	Standard	Standard	Standard
Door Ajar Alarm	Standard	Standard	Standard	Standard
Warranty	Two-year parts, labor, or full replacement	Two-year parts, labor, or full replacement	Two-year parts, labor, or full replacement	Two-year parts, labor, or full replacement